

### Caledonian


#### Mining Cables (ICEA & CSA Standard)

www.caledonian-cables.com marketing@caledonian-cables.com

#### Portable Power Cables

Type W Five-Conductor Round Portable Power Cable 2kV 5C4AWG





#### **APPLICATIONS**

These cables are designed for general use where bare grounding conductors are not required or desired.

#### **STANDARDS**

ICEA S-75-381/NEMA WC 58 ASTM B 172/ASTM B 33 CAN/CSA C22.2 No. 96

#### CABLE CONSTRUCTION

Conductors: Stranded annealed tinned copper conductor.

Insulation: Ethylene Propylene Rubber (EPR).

Jacket:Reinforced heavy-duty/extra-heavy-duty Chlorinated Polyethylene (CPE), black. (Cables having a nominal outside diameter of more than 2.0 inches require extra-heavy-duty jackets.)

#### Options:

Other jacket materials such as CSP/PCP/NBR/PVC are available upon request.

Two-layer jacket with reinforcing fibre between the two layers can be offered as an option.

#### **COLOUR CODE**

Conductor Identification According to ICEA S-75-381:

5 Cores:Black+White+Green+Red+Orange

#### PHYSICAL AND THERMAL PROPERTIES

Minimum Bending Radius: 6×OD

Maximum Conductor Operating Temperature: +90°C

#### **DIMENSION AND PARAMETERS**

No. of Cores	AWG Size	Strands	Nominal Insulation Thickness	Insulation	Jacket	Jacket	Overall	Overall	Weight	Ampacity
			in	mm	in	mm	in	mm	kg/km	amps



# Caledonian

## Mining Cables (ICEA & CSA Standard)

www.caledonian-cables.com marketing@caledonian-cables.com

5	4	259	0.06	1.5	0.155	3.9	1.36	35.2	2131	88
---	---	-----	------	-----	-------	-----	------	------	------	----