


# Caledonian

Mining Cables (ICEA & CSA Standard) www.caledonian-cables.com marketing@caledonian-cables.com

#### Portable Power Cables

Type W Four-Conductor Round Portable Power Cable 2kV 4C250AWG





Reinforced CPE Jacket Stranded Tinned Copper Conductor

#### **APPLICATIONS**

These cables are designed for general use where bare grounding conductors are not required or desired.

#### **STANDARDS**

ICEA S-75-381/NEMA WC 58 **ASTM B 172/ASTM B 33** CAN/CSA C22.2 No. 96

#### CABLE CONSTRUCTION

Conductors:Stranded annealed tinned copper conductor. Insulation: Ethylene Propylene Rubber (EPR). Jacket:Reinforced heavy-duty/extra-heavy-duty Chlorinated Polyethylene (CPE), black. (Cables having a nominal outside diameter of more than 2.0 inches require extra-heavy-duty jackets.)

Options:

Other jacket materials such as CSP/PCP/NBR/PVC are available upon request. Two-layer jacket with reinforcing fibre between the two layers can be offered as an option.

## **COLOUR CODE**

Conductor Identification According to ICEA S-75-381: 4 Cores:Black+White+Green+Red

## PHYSICAL AND THERMAL PROPERTIES

Minimum Bending Radius: 6×OD Maximum Conductor Operating Temperature: +90°C

#### DIMENSION AND PARAMETERS

No. of Cores	AWG Size	Strands	Nominal Insulation Thickness	Insulation	Jacket	Jacket	Overall	Overall	Weight	Ampacity
			in	mm	in	mm	in	mm	kg/km	amps



# Caledonian

Mining Cables (ICEA & CSA Standard)

www.caledonian-cables.com marketing@caledonian-cables.com

4	250	627	0.095	2.4	0.235	6	2.66	67.6	8553	280
---	-----	-----	-------	-----	-------	---	------	------	------	-----