




# Caledonian

NEK606 Caledonian Offshore & Marine Cables Medium Voltage Power Cables

[www.caledonian-cables.com](http://www.caledonian-cables.com)

[marketing@caledonian-cables.com](mailto:marketing@caledonian-cables.com)

## P104 (Formerly P4 or P4/P11) RFOU/TFOU 8.7/15KV



### APPLICATIONS

These cables are flame retardant, low smoke, halogen free and mud resistant, used for fixed installation for medium voltage power.

### STANDARDS

IEC 60092-354  
IEC 60092-351  
IEC 60092-359  
IEC 60332-1  
IEC 60332-3-22  
IEC 60754-1,2  
IEC 61034-1,2  
NEK 606:2004

### VOLTAGE RATING

8.7/15KV

### CABLE CONSTRUCTION

Conductors: Circular tinned annealed stranded copper to IEC 60228 class 2.

Conductor Screen: Semi conducting material.

Insulation: Halogen-free EPR. XLPE can be offered as an option (for TFOU cable).

Insulation Screen: Semi conducting material and tinned copper wire braid.

Bedding: Halogen free compound.

Armour: Tinned copper wire braid.

Outer Sheath: Halogen free thermosetting compound, SHF2 (for TYPE P4), or halogen free mud resistant thermosetting compound, SHF MUD (for TYPE P4/P11), coloured red.

### MECHANICAL PROPERTIES

Bending Radius: 15×OD (during installation); 9×OD (fixed installed)

Temperature Range: -20°C ~ +90°C

### TECHNICAL CHARACTERISTICS



## Caledonian

### NEK606 Caledonian Offshore & Marine Cables Medium Voltage Power Cables

[www.caledonian-cables.com](http://www.caledonian-cables.com)

[marketing@caledonian-cables.com](mailto:marketing@caledonian-cables.com)

| Nom. Cross-Section Area | Nom. Conductor Diameter | Maximum DC Resistance @20°C | Continuous Current Rating @45°C 3/4 Core | Short Circuit Current 1s |
|-------------------------|-------------------------|-----------------------------|--|--------------------------|
| mm <sup>2</sup>         | mm                      | Ohm/km                      | A  | A                        |
| 240                     | 19.6                    | 0.0762                      | 365                                      | 34340                    |

#### DIMENSION AND PARAMETERS

| No. of Cores × Cross-sectional Area | Nominal Insulation Thickness | Nominal Inner Sheath Thickness | Nominal Outer Sheath Thickness | Approx. Overall Diameter | Nominal Copper Weight |
|-------------------------------------|------------------------------|--------------------------------|--------------------------------|--------------------------|-----------------------|
| No.×mm <sup>2</sup>                 | mm                           | mm                             | mm                             | mm                       | kg/km                 |
| 3×240                               | 4.5                          | 1.8                            | 4.0                            | 90.6                     | 15860                 |