





Caledonian

NEK606 Offshore & Marine Cables

www.caledonian-cables.com

marketing@caledonian-cables.com

P111 RU/TU (Formerly P18 RU) 0.6/1kV



APPLICATIONS

These cables are flame retardant, low smoke, halogen free and mud resistant, used for control, power and lighting systems.

STANDARDS

IEC 60092-353
IEC 60092-360
IEC 60332-1
IEC 60332-3-22
IEC 60754-1,2
IEC 61034-1,2
NEK 606:2016

VOLTAGE RATING

0.6/1KV

CABLE CONSTRUCTION

Conductors: Tinned annealed stranded copper to IEC 60228 class 2 or class 5.

Insulation: Halogen-free EPR or XLPE.

Outer Sheath: Halogen free thermosetting compound, SHF2, coloured black.

MECHANICAL PROPERTIES

Bending Radius: 8×OD (during installation); 6×OD (fixed installed)

Temperature Range: -20°C ~ +90°C

TECHNICAL CHARACTERISTICS

Nom. Cross-Section Area	Nom. Conductor Diameter	Maximum DC Resistance @20°C	Short Circuit Current 1s
mm ²	mm	Ohm/km	A
2.5	2.1	7.56	360

DIMENSION AND PARAMETERS



Caledonian

NEK606 Offshore & Marine Cables

www.caledonian-cables.com

marketing@caledonian-cables.com

No. of Cores × Cross-sectional Area	Nominal Insulation Thickness	Nominal Sheath Thickness	Approx. Overall Diameter	Approx. Weight
No.×mm ²	mm	mm	mm	kg/km
16×2.5	1.0	1.6	23.3	810