



Caledonian

Railway Cables



www.caledonian-cables.com

marketing@caledonian-cables.com

12/20(24)KV Power Cables to CENELEC HD620 & C 33-226

XKDT-YT Three Core 12/20KV Copper Conductor

RF33226-XKDT-YT-12/20KV-3G150SCU



APPLICATIONS

The cables are power cables for power networks, underground, outdoors and in cable ducting, in particular for installation where fire, smoke emission and toxic fumes create a potential threat.

STANDARDS

CENELEC HD 620

C 33-226

CABLE CONSTRUCTION

Conductor: Class 2 stranded plain copper conductor to BS EN 60228:2005(previously BS6360)

Conductor Screen: Semi-conducting material

Insulation: XLPE

Insulation Screen: Semi-conducting material

Metallic Screen: Copper wire screen

Filler: PETP (Polyethylene Terephthalate) fibres

Separator: Binding tape

Sheath: PE

PHYSICAL AND THERMAL PROPERTIES

Minimum Bending Radius: 12xOD

Temperature Range: 0°C to +90°C (during operation); 0°C to +60°C (during installation)

DIMENSION AND PARAMETERS

No. of Cores × Cross-sectional Area	No./Nominal Diameter of Strands	Nominal Insulation Thickness	Nominal Sheath Thickness	Nom. Overall Diameter	Approx. Weight	Max. DC Resistance at 20°C
No. × mm ²	no./mm	mm	mm	mm	kg/km	Ω/km
3 x 150	37/2.25	5.5	3.5	79	7450	0.124



Caledonian

Railway Cables

www.caledonian-cables.com


marketing@caledonian-cables.com



Buried in Ground




Laid In Ducts



UV Resistant



Water Resistant



Zero Halogen
IEC 60754-1/EN 50267-2-1
NF C20-454