



Caledonian



Railway Cables

www.caledonian-cables.com

marketing@caledonian-cables.com

CV /CVZ Indoor Equipment Cables

CV/CVZ Cables RS/CVZ-075-Y(4Y)-1C1S



APPLICATIONS

The cables are used as cabling wires for the relays and electronic equipments in the Traffic Control Center and Trackside Equipment Shelter. The CV cables are suitable for use only in Optical Control Panel (OCP) wiring.

STANDARDS

SNCF CT 500

VOLTAGE RATING

450/750V

CABLE CONSTRUCTION

Conductors: class 1 solid tinned copper.

Insulation: White unleaded PVC.

Sheath: Coloured polyamide outer sheath.

PHYSICAL AND THERMAL PROPERTIES

Minimum Bending Radius (static): 5xOD

Minimum Bending Radius (dynamic): 10xOD

Operating Temperature: -15°C to +70°C

DIMENSION AND PARAMETERS

No. of Conductor	Conductor Size	Conductor Diameter	Nominal Diameter over Insulation	Nominal Sheath Thickness	Nom. Overall Diameter	Approx. Weight	max. conductor resistance
	mm ²	mm	mm	mm	mm	kg/km	Ω/km
1	1	1.17	1.9	0.2	2.3	13.2	17.9




Caledonian

Railway Cables

www.caledonian-cables.com

marketing@caledonian-cables.com



Abrasion Retardant




Fire Retardant
NF C32-010-2,2(C1)
IEC60332-3-24 IEN50366-2-4



Mineral Oil Resistant



Rated voltage



Resistance To High Temperature



Water Resistant