




WTB (Wired Train Bus) Cables

FRL-WTB-02YCH-2C0.75



APPLICATIONS

The cables are designed for permanent installation inside of rolling stock to connect fixed parts. A typical application is a communication system in a locomotive. The system uses a wire backed bus system to the TCN standard for control and instrumentation and for diagnostics. This bus system consists of the rail bus WTB (Wired Train Bus) and the road bus MVB (Multifunction Vehicle Bus) which are connected via redundant gateways.

VOLTAGE RATING

300 V

CABLE CONSTRUCTION

Conductors: Stranded tinned copper conductor according to IEC 60228 class 5

Insulation: Foam PE or foam skin PE

Core Wrapping: Plastic tape(s)

EMC Screen: Tinned copper braid

Outer Sheath: Cross-linked oil resistant LSZH compound

MECHANICAL PROPERTIES

Max. Temperature: 90 °C

Min. Temperature: -40 °C

Bending Radius: 12 x Overall Diameter

CHEMICAL AND ENVIRONMENTAL PROPERTIE

EN 60684-2	No fluorine
EN 50305; EN 60811-2-1	Resistance to mineral oil & fuel oil, acid & alkali
EN 50305	Resistance to ozone

FIRE PERFORMANCE FOR ROLLING STOCK APPLICATION

EN 50306-2	Hazard levels HL1, HL2, HL3
DIN 5510-2	Protection level 1/2/3/4
BS 6853	Interior use 1a, 1b, II; Exterior use 1a, 1b, II
NF F 16-101	F0



Caledonian

Databus Cables

www.caledonian-cables.com

marketing@caledonian-cables.com

EN45545-2	R15 Interior/ R16 Exterior HL1, HL2, HL3
-----------	------------------------------------------

FIRE PERFORMANCE IN GENERAL

EN 50265-2-1; IEC 60332-1-2; NF C 32-070 2.1 (C2)	Vertical flame propagation for a single insulated wire or cable
EN 50266-2-4 + EN 50305; IEC 60332-3-24;NF C 32-070 2.2 (C1); VDE 0472 Teil 804	Vertical flame spread of vertically mounted bunched wires or cables
EN 50268-2; IEC 61034-2; NF C 32-073 ;NF C 20-902; NF F 16 101; VDE 0472 Teil 816	Low Smoke Emission
EN 50267-2-1; IEC 60754-1; NF C 32-074;NF C 20-454; VDE 0472 Teil 815	Halogen Free
EN 50267-2-2/3; IEC 60754-2; NF C 32-074;NF C 20-453; VDE 0472 Teil 813	Low Corrosivity (Acidity & Conductivity)
EN 50305; NF X 70-100; NF F 63 808; TM1-04; BS6853	Low Toxicity
NF F 63 808; BS6853; NF F 16 101	Smoke Index
EN45545-2	Requirement for fire behavior of materials & components R15/R16

DIMENSION AND PARAMETERS

No. of Cores × Cross-sectional Area	No./ Nominal Diameter of Strands	Nominal Sheath Thickness	Approx. Overall Diameter	Approx. Weight	Max. Conductance Resistance at 20 °C	Impedance @1-10MHz	Max. Transfer Impedance (Not more than 30Mhz)	Max. Attenuation (@1MHz)	Max. Attenuation (@1.5MHz)	Max. Attenuation (@2MHz)	Max. Attenuation (@3MHz)
No. ×mm ²	no./mm	mm	mm	kg/km	MΩ × km	Ω	μΩ/m	dB/Km	dB/Km	dB/Km	dB/Km
2×0.75	19/0.22	1.4	8.3	97	26.7	120+/-12	30	10	13	14	18



Caledonian

Databus Cables

www.caledonian-cables.com

marketing@caledonian-cables.com



Abrasion Retardant



Acid & Alkaline Resistant



Cold Resistant



Corona Resistant



Fire Retardant
NF C32-070-2, 2(C1)
IEC60332-3-24/EN50266-2-4



Flame Retardant
NF C32-070-2, 1(C2)
IEC60332-1-2/EN50265-2-1



Highly Flexible



IRM 902
Mineral Oil Resistant



IRM 903
Fuel Oil Resistant



Low Corrosivity
IEC60754-2/EN50267-2-2/3
NF C32-074/NF C20-453



Low Smoke Emission
IEC 61034-2 / EN 50268-2
NF C32-073/NF C 20-902



Low Toxicity
EN 50305; NF X70-100/NF
F63 808/TM1-04/BS 6853



Ozone Resistant



Resistance To Soldering Heat



UV Resistant



Zero Halogen
IEC 60754-1/EN 50267-2-1
NF C20-454