



Caledonian



Submersible Pump Cables for Oil Industry

www.caledonian-cables.com

marketing@caledonian-cables.com

284°F/140°C EPDM/NBR Round Electrical Submersible Pump Cable

QYENY-140-3kV-3G4AWG



APPLICATIONS

These cables are designed for transmitting power to the submersible motor in the oil industry, suitable for installed down well in the oil industry.

STANDARDS

IEEE Std. 1018

API RP 11S5

API RP 11S6

VOLTAGE RATING

3kV

CABLE CONSTRUCTION

Conductor: Solid/stranded copper conductor.

Insulation: EPDM insulation.

Optional Barrier: Tape, braid, tape and braid, or extruded barrier, used for fluid protection and hoop strength.

Jacket: Oil-resistant nitrile rubber.

Armor: Galvanized steel.

DIMENSION AND PARAMETERS

| No. of Cores | Conductor Size | AWG Size | Conductor Diameter | Conductor Diameter | Nominal Insulation Thickness | Nominal Insulation Thickness | Approx. Overall Diameter | Approx. Overall Diameter | Approx. Weight | Approx. Weight |
|--------------|-----------------|----------|--------------------|--------------------|------------------------------|------------------------------|--------------------------|--------------------------|----------------|----------------|
| | mm ² | | in | mm | in | mm | in | mm | kg/km | LBS/MFT |
| 3 | 21.1 | 4 | 0.204 | 5.182 | 0.075 | 1.9 | 1.22 | 31 | 1465 | 985 |