

Caledonian


Telephone Cables www.caledonian-cables.com

marketing@caledonian-cables.com

INDOOR TELEPHONE CABLES

PE/PVC Insulated Parallel Drop Wires to RUS (REA) PE-7 TP7-2Y-1P18A-SS





APPLICATIONS

The drop wires are designed for use in extending telephone circuits to subscriber premises by means of an aerial drop from distribution wire or cables. The shape may be in oval/dumbbell shape to aid in separation of conductors.

STANDARDS

RUS (REA) PE-7 ASTM B227, B452 & B1

CABLE CONSTRUCTION

Conductors: Two conductors made of 0.9/1.0/1.023mm copper covered steel wires serve dually as conductor and strength members.

Bonding: Bonding of the insulation to the conductors is made to assure the full conductor strength is transferred to the wire support clamps.

Insulation: Conductors are laid in a parallel configuration and covered with low density or medium density polyethylene (PE).

PHYSICAL AND THERMAL PROPERTIES

Temperature range during operation (fixed state): $-30^{\circ}C - +70^{\circ}C$ Temperature range during installation (mobile state): $-20^{\circ}C - +50^{\circ}C$ Minimum bending radius: 7.5 x Overall Diameter

DIMENSION AND PARAMETERS

aledonia Cable	No. of C Cores	Conducto Size		Conducto Diametel								Cable Woight
Cable	Coles	3126	Size			Thicknes	over	over	Diameter	Diameter		weight
							nsulation	nsulatior (min.)				
		mm²		mm	in	mm	mm	in	in	mm	Lbs./	kg/km
											Kft	



Caledonian

Telephone Cables www.caledonian-cables.com

marketing@caledonian-cables.com

TP7-2Y	2	0.827	18	1.023	0.04	1.02	3.06	0.118 (0.11x0.28	3x7	22	32
-1P18A												
-SS												