
Caledonian

VFD Cable

www.caledonian-cables.com marketing@caledonian-cables.com

VFD-Shielded Power Cable

4C4AWG



APPLICATIONS

These high performance VFD cables are for dynamic industrial applications that reduces the effects of electrical noise and corona discharge, while providing a low impedance path to ground to eliminate the potential damage.

CABLE CONSTRUCTION

Conductor: Stranded fine copper conductor.
Insulation: Oil resistant composite material, provide high dielectric, tensile and mechanical properties.
Fillers: Low friction, non-wicking fillers provide increased flexibility in dynamic applications.
Drain wire: Flat braid drain wire.
Braid: 100% coverage aluminum foil, overall 80% coverage tinned copper braid.
Sheath: Special TPE compound, oil, ozone, UV resistant, flame and heat resistant. All-weather flexibility.

COLOUR CODE

3 black cores+1 yellow/green.

PHYSICAL AND THERMAL PROPERTIES

CSA – 1000 Volt
CSA – FT-4
TC-ER – 600 Volt
Rated temperature – 90C

DIMENSION AND PARAMETERS

No. of Cores	AWG Size	Conductor Stranding	Drain Wire Size	Approx. Overall Diameter	Ampacity	Cable Weight
			AWG	in	amps	Lbs./Kft
4	4	413/30	14	1.19	95	1083