
Caledonian


FIREGUARD Flame Retardant Power & Control Cables

www.caledonian-cables.com marketing@caledonian-cables.com

600/1000V XLPE Insulated, PVC Sheathed,Armoured Power Cables to BS 5467 (Multicore)

FGD400 1RVMV-R (CU/XLPE/PVC/SWA/PVC 600/1000V Class 2) 12C1.5
BS Code: 6942X/6943X/6944X/6945X





APPLICATIONS

The cables are mainly used in power stations, mass transit underground passenger systems,airports,petrochemical plants, hotels, hospitals, and high-rise buildings. This product type is TUV approved.

STANDARDS

Basic design to BS 5467

APPROVALS

TUV Certification

FIRE PERFORMANCE

Flame Retardance (Single Vertical Wire Test)	BS EN 60332-1-2

VOLTAGE RATING

600/1000V

CABLE CONSTRUCTION

Conductor: Annealed copper wire, stranded according to BS EN 60228 class 2.
Insulation: Extruded XLPE GP 8 according to BS 7655-1.3.
Bedding: PVC.
Armouring: Galvanized steel wire.
Outer Sheath: PVC Type 9 according to BS 7655-4.2.
Outer Sheath Option: UV resistance, hydrocarbon resistance, oil resistance, anti rodent and anti termite properties can be offered as option. Compliance to fire performance standard (IEC 60332-1, IEC 60332-3, UL 1581, UL 1666 etc) depends on the oxygen index of the PVC compound and the overall cable design.
LSPVC can also be provided upon request.

COLOUR CODE

Core identification: White insulation with black printed numerals. (Other colors available upon request).

Caledonian

FIREGUARD Flame Retardant Power & Control Cables

www.caledonian-cables.com marketing@caledonian-cables.com

Sheath Colour: Black, other colours can be offered upon request.

PHYSICAL AND THERMAL PROPERTIES

Maximum temperature range during operation (XLPE): 90°C
Maximum short circuit temperature (5 Seconds): 250°C
Minimum bending radius:8 x Overall Diameter

Electrical Properties

Conductor Operating Temperature: 90°C
Ambient Temperature: 30°C

DIMENSION AND PARAMETERS

No. of Cores × Cross-sectional Area	Conductor Class	Nominal Insulation Thickness	Nominal Bedding Thickness	Nominal Sheath Thickness	Nominal Steel Wire Armour Diameter	Approx. Overall Diameter	Approx. Weight
No.×mm²		mm	mm	mm	mm	mm	kg/km
12x1.5	2	0.6	0.8	1.5	1.25	19.4	820

Current-Carrying Capacities (Amp) according to Current-Carrying Capacities (Amp) according to BS 7671:2008 table 4E4A

Conductor Cross-sectional Area	Ref. Method C One 1C cable, 1-phase a.c. or d.c.	Ref. Method C One 3C or 4C cable, 3-phase a.c.	Ref. Method D One 2C cable, 1-phase a.c. or d.c.	Ref. Method D One 3C or 4C cable, 3-phase a.c.	Ref. Method E One 2C cable, 1-phase a.c. or d.c.	Ref. Method E One 3C or 4C cable, 3-phase a.c.
mm²	A	A	A	A	A	A
1.5	27	23	25	21	29	25

Voltage Drop (Per Amp Per Meter) according to Current-Carrying Capacities (Amp) according to BS 7671:2008 table 4E4B

Nominal Cross sectional Area	2C cable, d.c.	2C cable, 1-phase a.c.	3C or 4C cable, 3-phase a.c.
mm²	mV/A/m	mV/A/m	mV/A/m
1.5	31	31	27



Rated voltage



BS 5467


Flame Retardancy
BS/EN/IEC 60332-1-2