
# Caledonian


FIREGUARD Flame Retardant Power & Control Cables

www.caledonian-cables.com marketing@caledonian-cables.com

## 600/1000V XLPE Insulated, PVC Sheathed,Armoured Power Cables to BS 5467 (Multicore)

FGD400 1RVMV-R (CU/XLPE/PVC/SWA/PVC 600/1000V Class 2) 7C2.5
BS Code: 6942X/6943X/6944X/6945X






## APPLICATIONS

The cables are mainly used in power stations, mass transit underground passenger systems,airports,petrochemical plants, hotels, hospitals, and high-rise buildings. This product type is TUV approved.

## STANDARDS

Basic design to BS 5467

## APPROVALS

TUV Certification

## FIRE PERFORMANCE

| | |
|---|---|
| Flame Retardance (Single Vertical Wire Test) | BS EN 60332-1-2 |

## VOLTAGE RATING

600/1000V

## CABLE CONSTRUCTION

Conductor: Annealed copper wire, stranded according to BS EN 60228 class 2.
Insulation: Extruded XLPE GP 8 according to BS 7655-1.3.
Bedding: PVC.
Armouring: Galvanized steel wire.
Outer Sheath: PVC Type 9 according to BS 7655-4.2.
Outer Sheath Option: UV resistance, hydrocarbon resistance, oil resistance, anti rodent and anti termite properties can be offered as option. Compliance to fire performance standard (IEC 60332-1, IEC 60332-3, UL 1581, UL 1666 etc) depends on the oxygen index of the PVC compound and the overall cable design.
LSPVC can also be provided upon request.

## COLOUR CODE

Core identification: White insulation with black printed numerals. (Other colors available upon request).

# Caledonian

FIREGUARD Flame Retardant Power & Control Cables

www.caledonian-cables.com marketing@caledonian-cables.com

Sheath Colour: Black, other colours can be offered upon request.

## PHYSICAL AND THERMAL PROPERTIES

Maximum temperature range during operation (XLPE): 90°C
Maximum short circuit temperature (5 Seconds): 250°C
Minimum bending radius:8 x Overall Diameter

## Electrical Properties

Conductor Operating Temperature: 90°C
Ambient Temperature: 30°C

## DIMENSION AND PARAMETERS

| No. of Cores × Cross-sectional Area | Conductor Class | Nominal Insulation Thickness | Nominal Bedding Thickness | Nominal Sheath Thickness | Nominal Steel Wire Armour Diameter | Approx. Overall Diameter | Approx. Weight |
|---|---|---|---|---|---|---|---|
| No.×mm² | | mm | mm | mm | mm | mm | kg/km |
| 7x2.5 | 2 | 0.7 | 0.8 | 1.4 | 0.9 | 17.1 | 730 |

## Current-Carrying Capacities (Amp) according to Current-Carrying Capacities (Amp) according to BS 7671:2008 table 4E4A

| Conductor Cross-sectional Area | Ref. Method C One 1C cable, 1-phase a.c. or d.c. | Ref. Method C One 3C or 4C cable, 3-phase a.c. | Ref. Method D One 2C cable, 1-phase a.c. or d.c. | Ref. Method D One 3C or 4C cable, 3-phase a.c. | Ref. Method E One 2C cable, 1-phase a.c. or d.c. | Ref. Method E One 3C or 4C cable, 3-phase a.c. |
|---|---|---|---|---|---|---|
| mm² | A | A | A | A | A | A |
| 2.5 | 36 | 31 | 33 | 28 | 39 | 33 |

## Voltage Drop (Per Amp Per Meter) according to Current-Carrying Capacities (Amp) according to BS 7671:2008 table 4E4B

| Nominal Cross sectional Area | 2C cable, d.c. | 2C cable, 1-phase a.c. | 3C or 4C cable, 3-phase a.c. |
|---|---|---|---|
| mm² | mV/A/m | mV/A/m | mV/A/m |
| 2.5 | 19 | 19 | 16 |



Rated voltage



BS 5467


Flame Retardancy
BS/EN/IEC 60332-1-2