



# Caledonian

## FIREGUARD Flame Retardant Power & Control Cables



www.caledonian-cables.com

marketing@caledonian-cables.com

### 600/1000V PVC Insulated, PVC Sheathed, Unarmoured Power Cables to IEC 60502 (3 Cores)

FGD400 1VV-R (CU/PVC/PVC 600/1000V Class 2)

VDE Code: NYY



### APPLICATIONS

The cables are mainly used in fixed installations in industrial areas, buildings and similar applications but not for burial in the ground, either directly or in ducts.

### STANDARDS

Basic design to IEC 60502-1

### FIRE PERFORMANCE

Flame Retardance (Single Vertical Wire Test)	IEC 60332-1
--	-------------

### VOLTAGE RATING

600/1000V

### CABLE CONSTRUCTION

Conductor: Annealed copper wire, stranded according to BS EN 60228 class 2.

Insulation: PVC/A according to IEC 60502-1.

Inner Covering Option: Extruded PVC or polymeric compound.

Outer Sheath: Extruded PVC Type ST1/ST2 according to IEC 60502-1.

Outer Sheath Option: UV resistance, hydrocarbon resistance, oil resistance, anti rodent and anti termite properties can be offered as option. Compliance to fire performance standard (IEC 60332-1, IEC 60332-3, UL 1581, UL 1666 etc) depends on the oxygen index of the PVC compound and the overall cable design. LSPVC can also be provided upon request.

### COLOUR CODE

Insulation Colour:

Three-core: Brown, black, grey. Alternatively, green-and-yellow, blue, brown

Note: Depending on their intended use, the cables might be subject to the core colour requirements specified in BS 7671 or other standards, or in statutory requirements.

Sheath Colour: Black, other colours can be offered upon request

### PHYSICAL AND THERMAL PROPERTIES



# Caledonian

## FIREGUARD Flame Retardant Power & Control Cables

www.caledonian-cables.com

marketing@caledonian-cables.com

Maximum temperature range during operation (PVC): 70°C

Maximum short circuit temperature (5 Seconds):

Conductor cross-section  $\leq 300 \text{ mm}^2$ : 160°C

Conductor cross-section  $> 300 \text{ mm}^2$ : 140°C

Minimum bending radius: 12 x Overall Diameter

### Electrical Properties

Conductor Operating Temperature: 70°C

Ambient Temperature: 30°C

### DIMENSION AND PARAMETERS

No. of Cores × Cross-sectional Area	Conductor Class	Nominal Insulation Thickness	Nominal Insulation Thickness (Earth)	Nominal Sheath Thickness	Approx. Overall Diameter	Approx. Weight
No. x mm <sup>2</sup>		mm	mm	mm	mm	kg/km
3x185/95	2	1.6	1.4	2.6	51.6	7321



Rated voltage



Flame Retardancy  
IEC 60332-1



IEC60502-1