





# Caledonian

Industrial Cables (Italian Standard)

[www.caledonian-cables.com](http://www.caledonian-cables.com)

[marketing@caledonian-cables.com](mailto:marketing@caledonian-cables.com)

## H07G-R



## APPLICATIONS

These cables are recommended for the internal wiring of switchboards and distributor boards as well as in operating parts in or on lights. The higher temperature range allows for connections to heaters with an alternating nominal voltage of 1000V. or direct nominal voltage of 750V. These cables are all allowed for laying in tubes in and under plaster.

## STANDARDS

CEI 20-19/7

CEI 20-35(EN60332-1)

HD 22.7 S2

## VOLTAGE RATING

450/750V

## CABLE CONSTRUCTION

- Solid bare copper / strands
- Strands to VDE-0295 Class-2, IEC 60228 Class-2
- Rubber compound type EI3 (EVA) to DIN VDE 0282 part 7 insulation
- Cores to VDE-0293 colors

## COLOUR CODE

Insulation Colour Code

Colour coded to VDE 0293

Single core - Black, Blue, Green/Yellow, Red, Yellow, White, Violet, Brown, Grey, Orange, Pink

## PHYSICAL AND THERMAL PROPERTIES

- Test voltage: 2500volts
- Flexing bending radius:  $7 \times \varnothing$
- Static bending radius:  $7 \times \varnothing$
- Flexing temperature:  $-25^{\circ}\text{C}$  to  $+110^{\circ}\text{C}$
- Static temperature:  $-40^{\circ}\text{C}$  to  $+110^{\circ}\text{C}$
- Short circuit temperature:  $+160^{\circ}\text{C}$
- Flame retardant: IEC 60332.1



# Caledonian

Industrial Cables (Italian Standard)

[www.caledonian-cables.com](http://www.caledonian-cables.com)

[marketing@caledonian-cables.com](mailto:marketing@caledonian-cables.com)

- Insulation resistance: 10 MΩ x km

## DIMENSION AND PARAMETERS

No. of Cores × Cross- sectional Area	AWG Size	Nominal Insulation Thickness	Approx. Overall Diameter	Nominal Copper Weight	Approx. Weight
No. × mm <sup>2</sup>		mm	mm	kg/km	kg/km
1 x 35	2(7/10)	1.4	10.3	336	360