




Caledonian

Industrial Cables (Australian Standard Low Voltage)

www.caledonian-cables.com

marketing@caledonian-cables.com

XLPE Insulated, PVC Sheathed Unarmored Multicore control Cables 0.6/1kV



APPLICATIONS

These cables are used for control circuits unenclosed, enclosed in conduit, buried direct or in underground ducts for commercial, industrial, mining and electricity authority systems where not subject to mechanical damage.

STANDARDS

AS/NZS 5000.1

AS/NZS 3008

AS/NZS 1125

APPROVALS

SAA Certification (SAA-173128-EA)

VOLTAGE RATING

0.6/1kV

CABLE CONSTRUCTION

Conductor: Plain annealed copper

Insulation: XLPE X-90

Sheath: Polyvinylchloride compound PVC 5V-90

COLOUR CODE

Insulation Colours: Red, White, Blue

Sheath Colours: Black, other colors are available upon request

TECHNICAL CHARACTERISTICS

Nom. Cross-Section Area	Current Ratings (Unenclosed In Air)	Current Ratings (Buried Direct)	Current Ratings (Buried In Ducts)	Maximum DC Resistance @20°C	Maximum AC Resistance @90°C	Reactance	Voltage Drop at Max Operating Temperature (Three Phase)
mm ²	A	A	A	Ohm/km	Ohm/km	Ohm/km	mV/A/m



Caledonian

Industrial Cables (Australian Standard Low Voltage)

www.caledonian-cables.com

marketing@caledonian-cables.com

10	68	91	68	1.83	2.33	0.084	4.05
----	----	----	----	------	------	-------	------

DIMENSION AND PARAMETERS

No. of Cores × Cross- sectional Area	No./Nominal Diameter of Strands	Nominal Insulation Thickness	Nominal Sheath Thickness	Approx. Overall Diameter	Approx. Weight
No. × mm ²	no./mm	mm	mm	mm	kg/km
3×10	7/1.35	0.7	1.4	15.3	435